

View Online at <https://aerobasegroup.com/nsn/5315-00-584-6567>

First End Style:

Oval

Second End Style:

Square

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.437 inches and 0.469 inches

Taper Length:

Between 0.859 inches and 0.891 inches

Taper Minor Diameter:

Between 0.315 inches and 0.319 inches

Taper Major Diameter:

0.350 inches

Grip Length:

Between 0.734 inches and 0.766 inches

Thready Qty Per Inch (tpi):

28

Second End Relationship With First End:

Not identical

Thread Size:

0.250 inches

Taper:

0.500 per foot in inches

First End Location:

Oval end

Material:

Steel comp 4037 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130

Material Specification:

An-s-9 federal standard 1st material response or an-qq-s-689 federal standard 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.