NSN 5315-00-584-6567



Threaded Tapered Pin - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5315-00-584-6567 First End Style: Oval **Second End Style:** Square **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.437 inches and 0.469 inches **Taper Length:** Between 0.859 inches and 0.891 inches **Taper Minor Diameter:** Between 0.315 inches and 0.319 inches **Taper Major Diameter:** 0.350 inches **Grip Length:** Between 0.734 inches and 0.766 inches Thready Qty Per Inch (tpi): 28 Second End Relationship With First End: Not identical **Thread Size:** 0.250 inches Taper: 0.500 per foot in inches First End Location: Oval end Material: Steel comp 4037 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 **Material Specification:**

An-s-9 federal standard 1st material response or an-qq-s-689 federal standard 1st material response or mil-s-6049 military specification 2nd material response or mil-s-6050 military specification 3rd material response or mil-s-6098 military specification 4th material response or mil-s-6758 military specification 5th material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 1, cl 3 federal specification single treatment response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

NSN 5315-00-584-6567

Threaded Tapered Pin - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6049 spec.