NSN 5315-00-597-5687

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-597-5687

| First End Style: | |
|--|--|
| Square | |
| Thread Class: | |
| 3a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 0.680 inches | |
| Shank Length: | |
| Between 0.530 inches and 0.590 inches | |
| Shoulder Diameter: | |
| Between 0.530 inches and 0.590 inches | |
| Shank Diameter: | |
| Between 0.312 inches and 0.322 inches | |
| Overall Length: | |
| Between 2.470 inches and 2.530 inches | |
| Internal Drive Style: | |
| Slot | |
| Second End Relationship With First End: | |
| Identical | |
| Thread Size: | |
| 0.375 inches | |
| Second Shank Diameter: | |
| Between 0.371 inches and 0.374 inches | |
| First End Location: | |
| Both ends | |
| Surface Finish: | |
| 125.000 microinches | |
| Second Shank Length: | |
| Between 1.160 inches and 1.220 inches | |
| Material: | |
| Steel comp 4130 | |
| Material Specification: | |
| Mil-s-6758 military specification single material response | |
| Style Designator: | |
| Shoulder | |
| Thread Series Designator: | |
| Unc | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 5315-00-597-5687

Headless Shoulder Pin - Page 2 of 2

AeroBase Group

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.