# NSN 5315-00-598-6558

Quick Release Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-598-6558

# Shank Diameter:

Between 0.3720 inches and 0.3735 inches

# **Detent Quantity:**

2

## Actuation Method:

Push button

## **End Application:**

Dw/s: support equipment (se), b-2 bomber; support equipment, c-130 aircraft; missile, mx peacekeeper; aircraft, galaxy c-5; strategic weapon sytems (poseidon and trident); guided missile, intercept

## Grip Length:

Between 4.000 inches and 4.020 inches

#### Actuation Type:

Push

#### Hardness Rating:

40.0 rockwell c spindle

#### Shoulder To Head End Distance:

1.450 inches

#### Pin Center To Handle End Distance:

Between 1.555 inches and 1.640 inches

#### Pin Attachment Type:

Hook or ring

#### **Detent To Tapered End Distance:**

Between 0.335 inches and 0.365 inches

#### Material:

Steel comp 630 spindle or steel comp 632 spindle

#### **Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

#### Surface Treatment:

Passivate spindle

#### **Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

#### Style Designator:

L handle

Shelf Life:

N/a

#### Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0