## NSN 5315-00-608-5249

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-608-5249

First End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.400 inches and 0.430 inches
Shank Length:
Between 1.010 inches and 1.050 inches
Shoulder Diameter:
0.216 inches
Shank Diameter:
Between 0.1665 inches and 0.1695 inches
Overall Length:
Between 1.470 inches and 1.490 inches
Internal Drive Style:
Slot
First End Taper Length:
Between 0.010 inches and 0.020 inches
Second End Relationship With First End:
Identical
Hardness Rating:
38.0 rockwell c and 43.0 rockwell c
First End Location:
Shank end
First End Taper Angle:
45.0 degrees
Criticality Code Justification:
Aaze
Surface Finish:
125.000 microinches
Material:
Steel comp 4140 and steel comp 8640
Surface Treatment:
Phosphate
Style Designator:
Shoulder
Shelf Life:
N/a
Unit Of Measure:

## NSN 5315-00-608-5249

Headless Shoulder Pin - Page 2 of 2

Demilitarization:

No

Fiig:

A212a0

