

View Online at <https://aerobasegroup.com/nsn/5315-00-625-5773>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.484 inches and 0.516 inches

**Shank Length:**

Between 0.547 inches and 0.578 inches

**Shoulder Width Across Flats:**

Between 0.484 inches and 0.516 inches

**Shank Diameter:**

Between 0.248 inches and 0.250 inches

**Overall Length:**

Between 1.359 inches and 1.391 inches

**Undercut Diameter:**

0.036 inches

**Undercut Width:**

Between 0.047 inches and 0.078 inches

**Second Undercut Width:**

Between 0.047 inches and 0.078 inches

**Second Undercut Diameter:**

0.036 inches

**First End Taper Length:**

Between 0.047 inches and 0.078 inches

**Second End Taper Length:**

Between 0.047 inches and 0.078 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.312 inches

**Second Shank Diameter:**

Between 0.297 inches and 0.328 inches

**First End Location:**

Large end

**First End Taper Angle:**

Between 44.0 degrees and 46.0 degrees

**Second End Taper Angle:**

Between 44.0 degrees and 46.0 degrees

**Second Shank Length:**

Between 0.672 inches and 0.703 inches

**Material:**

Steel comp 416

**Material Specification:**

Qq-s-763, cond a federal specification single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Undercut

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0