

View Online at <https://aerobasegroup.com/nsn/5315-00-628-4001>

**Head Diameter:**

Between 0.510 inches and 0.630 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Ring Handle Diameter:**

Between 1.000 inches and 1.125 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Wsd: tank, m-60 series; aircraft, airlifter c-17a; tacsatcom, an/tsc-85 and an/tsc-93; fighting vehicle systems, bradley (bfvs)

**Grip Length:**

Between 1.200 inches and 1.220 inches

**Actuation Type:**

Pull and push

**Hardness Rating:**

36.0 rockwell c spindle and 40.0 rockwell c spindle

**Shear Strength:**

20600 double pounds per square inch

**Shoulder To Head End Distance:**

1.000 inches

**Pin Attachment Type:**

Link or ring

**Detent To Tapered End Distance:**

0.510 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Ring handle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0