

View Online at <https://aerobasegroup.com/nsn/5315-00-628-4001>

Head Diameter:

Between 0.510 inches and 0.630 inches

Shank Diameter:

Between 0.3720 inches and 0.3735 inches

Ring Handle Diameter:

Between 1.000 inches and 1.125 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Wsd: tank, m-60 series; aircraft, airlifter c-17a; tacsatcom, an/tsc-85 and an/tsc-93; fighting vehicle systems, bradley (bfvs)

Grip Length:

Between 1.200 inches and 1.220 inches

Actuation Type:

Pull and push

Hardness Rating:

36.0 rockwell c spindle and 40.0 rockwell c spindle

Shear Strength:

20600 double pounds per square inch

Shoulder To Head End Distance:

1.000 inches

Pin Attachment Type:

Link or ring

Detent To Tapered End Distance:

0.510 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Ring handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0