

View Online at <https://aerobasegroup.com/nsn/5315-00-633-7639>

**First End Style:**

Chamfered

**Head Style:**

Round w/wrench flats

**Under Head Length:**

1.024 inches

**First Step Diameter:**

0.312 inches

**First Step Length:**

0.449 inches

**Second Step Diameter:**

Between 0.301 inches and 0.306 inches

**Second Step Length:**

0.010 inches

**Third Step Diameter:**

Between 0.187 inches and 0.188 inches

**Third Step Length:**

Between 0.300 inches and 0.310 inches

**Hole Arrangement Style:**

Both end drilled

**First Hole Diameter:**

0.166 inches

**Second Hole Diameter:**

0.166 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.156 inches

**Center To Center Distance Between Holes:**

0.562 inches

**First End Taper Length:**

0.016 inches

**Width Across Flats:**

0.438 inches

**First End Taper Angle:**

0.016 radians

**Pin Head Diameter:**

Between 0.844 inches and 0.874 inches

**Height:**

0.085 inches

**Material:**

Aluminum alloy 6061

**Material Specification:**

Qq-a-325 federal specification single material response

**Surface Treatment:**

Anodize

**Surface Treatment Specification:**

Mil-a-8625, type 1 military specification single treatment response

**Style Designator:**

Shoulder

**Specification Data:**

08687-868328 manufacturers specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-a-8625 spec.