NSN 5315-00-664-1730

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-664-1730

First End Style:
Chamfered
Overall Length:
Between 3.255 inches and 3.275 inches
Diameter:
Between 0.498 inches and 0.499 inches
Effective Length:
Between 3.000 inches and 3.015 inches
Undercut Diameter:
Between 0.296 inches and 0.306 inches
Undercut Width:
Between 0.070 inches and 0.075 inches
Second Undercut Width:
Between 0.070 inches and 0.075 inches
Undercut Radius:
0.350 inches
First End Taper Length:
0.031 inches
Second End Relationship With First End:
Identical
Hardness Rating:
40.0 rockwell c and 45.0 rockwell c
First End Location:
Both ends
First End Taper Angle:
45.0 degrees
Material:
Steel
Surface Treatment:
Phosphate manganese
Surface Treatment Specification:
Mil-c-16232, type 1 military specification single treatment response
Style Designator:
Groove
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A212a0

NSN 5315-00-664-1730

Headless Grooved Pin - Page 2 of 2

Mil-std (military Standard):

Mil-c-16232 spec.

