NSN 5315-00-664-1943



Headless Shoulder Pin - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5315-00-664-1943
First End Style:
Chamfered
Second End Style:
Chamfered
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.822 inches
Shank Length:
0.775 inches
Shoulder Width Across Flats:
0.875 inches
Shank Diameter:
Between 0.311 inches and 0.312 inches
Overall Length:
1.680 inches
First End Taper Length:
0.060 inches
Second End Taper Length:
0.080 inches
Second End Relationship With First End:
Not identical
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Thread Size:
0.375 inches
Second Shank Diameter:
Between 0.368 inches and 0.375 inches
First End Location:
Shank end
First End Taper Angle:
45.0 degrees
Second End Taper Angle:
45.0 degrees
Second Shank Length:
0.905 inches
Material:
Steel
Material Specification:
Mil-s-6050 cond f4 military specification single material response

NSN 5315-00-664-1943

Headless Shoulder Pin - Page 2 of 2

Style Designator:

Shoulder

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6050 spec.

