

View Online at <https://aerobasegroup.com/nsn/5315-00-664-8575>

First End Style:

Chamfered

Head Style:

Flat

Diameter:

Between 0.5007 inches and 0.5011 inches

Undercut Diameter:

Between 0.451 inches and 0.491 inches

Under Head Length:

Between 0.680 inches and 0.700 inches

Undercut Radius:

Between 0.005 inches and 0.025 inches

First End Taper Length:

Between 0.115 inches and 0.135 inches

Hardness Rating:

44.0 rockwell c and 48.0 rockwell c

First End Taper Angle:

5.0 degrees

Pin Head Diameter:

Between 0.600 inches and 0.610 inches

Surface Finish:

20.0 microinches grip

Height:

Between 0.050 inches and 0.060 inches

Material:

Steel comp e52100

Material Specification:

Mil-s-7420 military specification single material response

Surface Treatment:

Oxide

Surface Treatment Specification:

Mil-c-13924, cl 1 military specification single treatment response

Style Designator:

Groove

Test Data Document:

81349-mil-i-6868 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-7420 spec.