NSN 5315-00-664-8633

Headless Shoulder Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-664-8633

Chamfered Second End Style: Round Shank Length: 0.520 inches Shudder Diameter: Any acceptable Shank Diameter: Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Catents: 0.300 inches Second End Outer Radius: 0.370 inches Material: Second Shank Length: 0.370 inches Material: Steel comp 8740 Material: Syle Designator: Shoulder Shoulder Shoulder Shoulder Shoulder Shoulder Shoulder Shoulder <td< th=""><th></th><th></th></td<>		
Second End Style: Round Shank Length: 0.520 inches Shoulder Diameter: Any acceptable Shank Diameter: Between 0.2439 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 3.370 inches Material: Steel com 8740 Material: Steel com 8740 Material Shoulder	First End Style:	
Round Shank Length: 0.520 inches Shoulder Diameter: Any acceptable Shank Diameter: Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long and First End Caper Angle: 45.0 dogrees Second End Outer Radius: 0.010 inches Gotto Shank Length: 0.370 inches Material Second Shank Length: 0.370 inches Material Specification: Arterial Specification: Naterial Specification: Shoulder Shoulder Haterial Specification: Naterial Specification: Naterial Specification: Naterial Specification: Naterial Specification:		
Shank Length: 0.520 inches Shoulder Diameter: Any acceptable Shank Diameter: Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Location: Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material Steel comp 8740 Material Specification: Ams 6322 asın standard single material response Style Designator: Shoulder Sheif Life: Na Unit Of Measure: - Pemilitarization: Na		
0.520 inchesShoulder Diameter:Any acceptableShank Diameter:Between 0.2493 inches and 0.2498 inchesOverall Length:0.950 inchesFirst End Taper Length:Any acceptableSecond End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Taper Angle:Long endFirst End Taper Angle:3.0 iochesSecond Shank Length:0.10 inchesBetween 0.2703 inches and 0.2708 inchesFirst End Taper Angle:1.5.0 degreesSecond Shank Length:0.370 inchesBetween 0.2703 inchesSecond Shank Length:0.370 inchesSecond Shank Length:0.370 inchesMaterial:Stel comp 8740Material Specification:Ams 6322 asen standard single material responseShyle Designator:ShoulderShoulderShelf Life:NaMaterial:ShoulderShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:NaShelf Life:Shelf Life:Shelf Life:Shelf Life:Shelf Life:Shelf Life:Shelf Life:Shelf Life:		
Shoulder Diameter:Any acceptableShank Diameter:Between 0.2493 inches and 0.2498 inchesOverall Length:0.950 inchesFirst End Taper Length:Any acceptableSecond End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Taper Angle:45.0 degreesSecond Shank Length:0.370 inchesBetween 0.2703 inchesFirst End Taper Angle:45.0 degreesSecond Shank Length:0.370 inchesBetween 0.2703 inchesSecond Shank Length:0.370 inchesSecond Shank Length:0.370 inchesSecond Shank Length:0.370 inchesMaterialSecond Shank Length:0.370 inchesMaterial Specification:Ams 6322 assn standard single material responseShulderShulderShulderShulderShulderNaDid Measure:Pomilitatization:NoFig:		
Any acceptable Shank Diameter: Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designato: Shoulder		
Shank Diameter: Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second Shank Length: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Image: No Fig:		
Between 0.2493 inches and 0.2498 inches Overall Length: 0.950 inches First End Taper Length: Any acceptable Becond End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second Shank Length: 0.370 inches Material: Steel comp 8740 Material: Shoulder Shoulder <	Any acceptable	
Overall Length:0.950 inchesFirst End Taper Length:Any acceptableSecond End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond Shank Length:0.010 inches370 inchesMaterial:Steel comp 8740Material Specification:Ans 6322 assn standard single material responseSyle Designator:ShoulderShoulderMaterial:NoFirst Life:N/aDemlitarization:NaFirst End Specification:NaShoulderShoulderShoulderShoulderFirst End:NaFirst End:NaShoulder:Shoulder:First:NaFirst:Hardin:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:Shoulder:First:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Shoulde:Sho	Shank Diameter:	
0.950 inchesFirst End Taper Length:Any acceptableSecond End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond Shank Length:0.010 inchesSecond Shank Length:0.370 inchesMaterial:Stel comp 8740Material Specification:Ans 6322 assn standard single material responseStyle Designator:NaMit of Measure:NaDird Otter Ratius:NaShoulder <th>Between 0.2493 inches and 0.2498 inches</th> <th></th>	Between 0.2493 inches and 0.2498 inches	
First End Taper Length:Any acceptableSecond End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond Shank Length:0.010 inchesMaterial:Steel comp 8740Material Specification:Ans 6322 assn standard single material responseStyle Designator:NaiderNaiderMaterial:NaiderShoulder<	Overall Length:	
Any acceptable Second End Relationship With First End: Not identical Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second Shank Length: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material: Shoulder	0.950 inches	
Second End Relationship With First End:Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.010 inchesSecond Shank Length:0.370 inchesMaterial:Steel comp 8740Material Specification:Ans 6322 assn standard single material responseShulderShulderShulderInf of Measure:NaDir of Measure:TFirst End EnderNaFirst End Specification:NaShulderShulderShulderShulderShulderFirst End EnderNaFirst End EnderFirst End EnderFirst End Specification:NaShulderShulderShulderFirst End EnderFirst End EnderFirst End EnderFirst End EnderFirst Ender </th <th>First End Taper Length:</th> <th></th>	First End Taper Length:	
Not identicalHardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.010 inchesSecond Shank Length:0.370 inchesMaterial:Steel comp 8740Material Specification:Ans 6322 assn standard single material responseSyle Designator:ShoulderInit of Measure:Pamiltarization:NaFig:	Any acceptable	
Hardness Rating:26.0 rockwell c and 32.0 rockwell cSecond Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.010 inchesSecond Shank Length:0.370 inchesMaterial:Steel comp 8740Material Specification:Anne 6322 assn standard single material responseStyle Designator:ShoulderInit of Measure:\rTotal Taper Angle:Total Taper Angle:Shell Life:N/aFinit End Taper Angle:Shell Life:N/aFinit End Ender:NaFinit End Ender:NaFinit End Ender:NaFinit Ender:NaFinit Ender:Shell Life:Shell Life:	Second End Relationship With First End:	
26.0 rockwell c Second Shank Diameter: Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: 0.370 inches Material: Steel comp 8740 Material Specification: Arms 6322 assn standard single material response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: - - Demilitarization: No	Not identical	
Second Shank Diameter:Between 0.2703 inches and 0.2708 inchesFirst End Location:Long endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.010 inchesBecond Shank Length:0.370 inchesMaterial:Steel comp 8740Material Specification:Arns 6322 assn standard single material responseStyle Designator:ShoulderDeniltarization:rPist of Measure:rFig:NaFig:	Hardness Rating:	
Between 0.2703 inches and 0.2708 inches First End Location: Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	26.0 rockwell c and 32.0 rockwell c	
First End Location:Long endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.010 inchesSecond Shank Length:0.370 inchesMaterial:Steel comp 8740Material Specification:Ams 6322 assn standard single material responseStyle Designator:ShoulderShoulderDemilitarization:Fig:	Second Shank Diameter:	
Long end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Ditt Of Measure: Ferlitien: No Fig:	Between 0.2703 inches and 0.2708 inches	
First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Sheff Life: N/a Init Of Measure: - Penilitarization: No Fig:	First End Location:	
45.0 degrees Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shoulder Int Of Measure: Demilitarization: No Fig:	Long end	
Second End Outer Radius: 0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shoulder Shoulder Ma Demilitarization: No Fig:	First End Taper Angle:	
0.010 inches Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No	45.0 degrees	
Second Shank Length: 0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No	Second End Outer Radius:	
0.370 inches Material: Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.010 inches	
Material:Steel comp 8740Material Specification:Ams 6322 assn standard single material responseStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Second Shank Length:	
Steel comp 8740 Material Specification: Ams 6322 assn standard single material response Style Designator: Shoulder Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No	0.370 inches	
Material Specification:Ams 6322 assn standard single material responseStyle Designator:ShoulderShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:	
Ams 6322 assn standard single material response Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Steel comp 8740	
Style Designator: Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Material Specification:	
Shoulder Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Ams 6322 assn standard single material response	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Style Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	Shoulder	
Unit Of Measure: Demilitarization: No Fiig:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
4040.0	Fiig:	
A212a0	A212a0	