

View Online at <https://aerobasegroup.com/nsn/5315-00-664-9330>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.488 inches and 0.508 inches

**Shank Length:**

Between 0.050 inches and 0.070 inches

**Shoulder Width Across Flats:**

Between 0.490 inches and 0.510 inches

**Shank Diameter:**

Between 0.3737 inches and 0.3742 inches

**Overall Length:**

Between 1.220 inches and 1.280 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.105 inches and 0.110 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.176 inches and 0.196 inches

**First End Taper Length:**

Between 0.020 inches and 0.040 inches

**Second End Taper Length:**

Between 0.030 inches and 0.050 inches

**Second End Relationship With First End:**

Not identical

**Thread Size:**

0.375 inches

**Second Shank Diameter:**

Between 0.3737 inches and 0.3742 inches

**First End Location:**

Short shank end

**First End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Surface Finish:**

63.000 microinches

**Second End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Second Shank Length:**

Between 0.800 inches and 0.820 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.