NSN 5315-00-678-6584

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-678-6584

| First End Style: |
|--|
| Chamfered |
| Second End Style: |
| Oval |
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.745 inches |
| Taper Length: |
| Between 3.109 inches and 3.141 inches |
| Taper Minor Diameter: |
| Between 0.508 inches and 0.510 inches |
| Taper Major Diameter: |
| Any acceptable |
| Hole Arrangement Style: |
| One end drilled |
| First Hole Diameter: |
| 0.106 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.280 inches |
| First End Taper Length: |
| 0.050 inches |
| Grip Length: |
| Any acceptable |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.437 inches |
| Taper: |
| 0.500 per foot in inches |
| First End Location: |
| Threaded end |
| First End Taper Angle: |
| 45.0 degrees |
| Second End Outer Radius: |
| Between 0.734 inches and 0.766 inches |
| Special Features: |
| Circular groove 0.300 in. Dia, 1.755 in. W, 0.750 in. From large end |
| Material: |
| Titanium alloy |
| |

NSN 5315-00-678-6584

Threaded Tapered Pin - Page 2 of 2



Material Specification:

Mil-t-9047d, type 3, cond a military specification single material response

Style Designator:

Threaded at small end

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-9047d spec.