NSN 5315-00-685-6464

Quick Release Pin - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5315-00-685-6464 |
|--|
| Handle Length: |
| Between 2.220 inches and 2.345 inches |
| Shank Diameter: |
| Between 0.497 inches and 0.498 inches |
| Detent Quantity: |
| 2 |
| Actuation Method: |
| Push button |
| Grip Length: |
| Between 1.750 inches and 1.770 inches |
| Actuation Type: |
| Push |
| Hardness Rating: |
| 58.0 rockwell c detent and 62.0 rockwell c detent |
| Shear Strength: |
| 36800 double pound |
| Shoulder To Head End Distance: |
| 1.600 inches |
| Pin Attachment Type: |
| Hook or ring |
| Detent To Tapered End Distance: |
| Between 0.430 inches and 0.460 inches |
| Material: |
| Steel comp 630 spindle |
| Material Specification: |
| Qq-w-423 federal specification single material response hook |
| Surface Treatment: |
| Passivate spring |
| Surface Treatment Specification: |
| Mil-s-5002 military specification single treatment response spring |
| Style Designator: |
| T handle |
| Specification Data: |
| 81349-mil-p-23460 government specification |
| Specification Or Standard: |
| 1 type and 2 style |
| Departure From Cited Document: |
| As modified by grip length |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5315-00-685-6464

Quick Release Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-a-8625 spec.