## NSN 5315-00-687-5734

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-687-5734

| First End Style:   |
|--|
| Chamfered  |
|  |
| Overall Length:  Between 1.594 inches and 1.625 inches                 |
| Diameter:  |
| Between 0.374 inches and 0.375 inches                                  |
|  |
| Effective Length:  |
| Between 1.312 inches and 1.344 inches                                  |
| Undercut Diameter:   |
| Between 0.350 inches and 0.354 inches                                  |
| Undercut Width:  |
| Between 0.028 inches and 0.031 inches                                  |
| Second Undercut Width:   |
| Between 0.028 inches and 0.031 inches                                  |
| Undercut Radius:   |
| 0.005 inches   |
| First End Taper Length:  |
| Between 0.052 inches and 0.072 inches                                  |
| Second End Relationship With First End:                                |
| Identical  |
| Hardness Rating:   |
| 58.0 rockwell c  |
| First End Location:  |
| Both ends  |
| First End Taper Angle:   |
| Between 40.0 degrees and 50.0 degrees                                  |
| Surface Finish:  |
| 63.0 microinches shank end   |
| Material:  |
| Steel comp 1118  |
| Material Specification:  |
| Aisi assn standard single material response                            |
| Surface Treatment:   |
| Cadmium  |
| Surface Treatment Specification:                                       |
| Qq-p-416, type 2, cl 3 federal specification single treatment response |
| Style Designator:  |
| Groove   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| _  |

--

## NSN 5315-00-687-5734

Headless Grooved Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0