

View Online at <https://aerobasegroup.com/nsn/5315-00-702-1086>

Handle Length:

Between 2.220 inches and 2.345 inches

Shank Diameter:

Between 0.4970 inches and 0.4985 inches

Detent Quantity:

2

Actuation Method:

Push button

Grip Length:

Between 2.500 inches and 2.520 inches

Actuation Type:

Push

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Shear Strength:

32800 double pounds per square inch

Shoulder To Head End Distance:

1.600 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.430 inches and 0.460 inches

Special Features:

Steel attaching hook or ring with specification qq-w-428 or qq-w-423, comp 302 with cadmium or passivated surface treatment with specification qq-p-416, type 2, cl 3 or qq-p-35

Material:

Steel spring

Material Specification:

Qq-w-470 federal specification single material response spring

Surface Treatment:

Passivate detent

Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response shank

Style Designator:

T handle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-t-6736 spec.