NSN 5315-00-702-1086

Quick Release Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-702-1086 Handle Length: Between 2.220 inches and 2.345 inches **Shank Diameter:** Between 0.4970 inches and 0.4985 inches **Detent Quantity: Actuation Method:** Push button **Grip Length:** Between 2.500 inches and 2.520 inches **Actuation Type:** Push **Hardness Rating:** 36.0 rockwell c and 40.0 rockwell c **Shear Strength:** 32800 double pounds per square inch **Shoulder To Head End Distance:** 1.600 inches Pin Attachment Type: Hook or ring **Detent To Tapered End Distance:** Between 0.430 inches and 0.460 inches **Special Features:** Steel attaching hook or ring with specification qq-w-428 or qq-w-423, comp 302 with cadmium or passivated surface treatment with specification qq-p-416, type 2, cl 3 or qq-p-35 Material: Steel spring **Material Specification:** Qq-w-470 federal specification single material response spring **Surface Treatment:** Passivate detent **Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response shank **Style Designator:** T handle Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Fiig:

No

A212a0

NSN 5315-00-702-1086

Quick Release Pin - Page 2 of 2



Mil-std (military Standard):

Mil-t-6736 spec.