

View Online at <https://aerobasegroup.com/nsn/5315-00-702-9128>

First End Style:

Chamfered

Second End Style:

Chamfered

Pinlength:

Between 0.428 inches and 0.448 inches

Pindiameter:

Between 0.1259 inches and 0.1261 inches

First End Corner Radius:

Between 0.016 inches and 0.047 inches

Second End Corner Radius:

Between 0.016 inches and 0.047 inches

First End Taper Length:

Between 0.016 inches and 0.047 inches

Second End Taper Length:

0.021 inches

Features Provided:

Casehardened

Second End Relationship With First End:

Not identical

Hardness Rating:

58.0 rockwell c and 64.0 rockwell c

First End Taper Angle:

Between 20.0 degrees and 30.0 degrees

Surface Finish:

16.0 microinches outside diameter

Second End Taper Angle:

Between 4.0 degrees and 12.0 degrees

Special Features:

Small chamfer end may be 0.016 in. Min, 0.047 in. Maximum radius in lieu of chamfer

Material:

Steel

Material Specification:

66 federal standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416 ty2 cl3 federal specification single treatment response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A212a0