

View Online at <https://aerobasegroup.com/nsn/5315-00-702-9128>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Pinlength:**

Between 0.428 inches and 0.448 inches

**Pindiameter:**

Between 0.1259 inches and 0.1261 inches

**First End Corner Radius:**

Between 0.016 inches and 0.047 inches

**Second End Corner Radius:**

Between 0.016 inches and 0.047 inches

**First End Taper Length:**

Between 0.016 inches and 0.047 inches

**Second End Taper Length:**

0.021 inches

**Features Provided:**

Casehardened

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

58.0 rockwell c and 64.0 rockwell c

**First End Taper Angle:**

Between 20.0 degrees and 30.0 degrees

**Surface Finish:**

16.0 microinches outside diameter

**Second End Taper Angle:**

Between 4.0 degrees and 12.0 degrees

**Special Features:**

Small chamfer end may be 0.016 in. Min, 0.047 in. Maximum radius in lieu of chamfer

**Material:**

Steel

**Material Specification:**

66 federal standard single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416 ty2 cl3 federal specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0