

View Online at <https://aerobasegroup.com/nsn/5315-00-705-1600>

**First End Style:**

Chamfered

**Head Style:**

Flat chamfer

**Diameter:**

Between 0.306 inches and 0.311 inches

**Effective Length:**

Between 0.7665 inches and 0.7865 inches

**Undercut Diameter:**

Between 0.234 inches and 0.266 inches

**Under Head Length:**

Between 0.953 inches and 0.984 inches

**Undercut Radius:**

Between 0.026 inches and 0.046 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.1094 inches and 0.1194 inches

**Distance From Centerline Of Hole To End Of Pin:**

Between 0.141 inches and 0.172 inches

**First End Taper Length:**

Between 0.062 inches and 0.094 inches

**Grip Length:**

Between 0.797 inches and 0.828 inches

**Features Provided:**

Casehardened

**First End Taper Angle:**

Between 12.0 degrees and 18.0 degrees

**Pin Head Diameter:**

Between 0.422 inches and 0.453 inches

**Height:**

Between 0.078 inches and 0.109 inches

**Material:**

Steel

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, type 2. CI 3 federal specification single treatment response

**Style Designator:**

Groove

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0