

View Online at <https://aerobasegroup.com/nsn/5315-00-705-1600>

First End Style:

Chamfered

Head Style:

Flat chamfer

Diameter:

Between 0.306 inches and 0.311 inches

Effective Length:

Between 0.7665 inches and 0.7865 inches

Undercut Diameter:

Between 0.234 inches and 0.266 inches

Under Head Length:

Between 0.953 inches and 0.984 inches

Undercut Radius:

Between 0.026 inches and 0.046 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.1094 inches and 0.1194 inches

Distance From Centerline Of Hole To End Of Pin:

Between 0.141 inches and 0.172 inches

First End Taper Length:

Between 0.062 inches and 0.094 inches

Grip Length:

Between 0.797 inches and 0.828 inches

Features Provided:

Casehardened

First End Taper Angle:

Between 12.0 degrees and 18.0 degrees

Pin Head Diameter:

Between 0.422 inches and 0.453 inches

Height:

Between 0.078 inches and 0.109 inches

Material:

Steel

Surface Treatment:

Cadmium

Surface Treatment Specification:

Qq-p-416, type 2. Cl 3 federal specification single treatment response

Style Designator:

Groove

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0