## NSN 5315-00-716-2636

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-716-2636 First End Style: Chamfered **Shank Length:** 0.518 inches **Shoulder Diameter:** Between 0.465 inches and 0.470 inches **Shank Diameter:** Between 0.3575 inches and 0.3585 inches **Overall Length:** Between 1.420 inches and 1.430 inches **Undercut Diameter:** Between 0.350 inches and 0.355 inches **Undercut Width:** Between 0.047 inches and 0.078 inches **Second Undercut Width:** Between 0.250 inches and 0.266 inches **Second Undercut Diameter:** Between 0.354 inches and 0.359 inches First End Taper Length: Between 0.016 inches and 0.047 inches **Second End Relationship With First End:** Identical **Hardness Rating:** 55.0 rockwell d and 60.0 rockwell d **Second Shank Diameter:** Between 0.365 inches and 0.370 inches **First End Location:** Both ends First End Taper Angle: 45.0 degrees **Second Shank Length:** 0.525 inches Material: Steel comp 1050 **Material Specification:** Mil-s-13502 military specification single material response **Style Designator:** Undercut Shelf Life: N/a

Unit Of Measure:

## NSN 5315-00-716-2636

Headless Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-13502 spec.