

View Online at <https://aerobasegroup.com/nsn/5315-00-723-2463>

Shank Diameter:

Between 0.2470 inches and 0.2485 inches

Button Handle Diameter:

Between 0.720 inches and 0.800 inches

Detent Quantity:

2

Actuation Method:

Push button

End Application:

Helicopter, mh-53e; aircraft, c-2a (reprocured); aircraft, tomcat f-14; aircraft, b-2 bomber (atb); helicopter, search and rescue, hh-60h; helicopter, carrier based asw, sh-60f; missile, minuteman lgm-30; helicopter, uscg search and rescue, hh-60j; aircraft, viking s-3b

Grip Length:

Between 1.200 inches and 1.220 inches

Actuation Type:

Push

Hardness Rating:

40.0 rockwell c spindle

Shoulder To Head End Distance:

0.890 inches

Pin Attachment Type:

Hook or ring

Detent To Tapered End Distance:

Between 0.260 inches and 0.290 inches

Material:

Steel comp 630 spindle or steel comp 632 spindle

Material Specification:

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

Surface Treatment:

Passivate spindle

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response spindle

Style Designator:

Button

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0