

View Online at <https://aerobasegroup.com/nsn/5315-00-723-2463>

**Shank Diameter:**

Between 0.2470 inches and 0.2485 inches

**Button Handle Diameter:**

Between 0.720 inches and 0.800 inches

**Detent Quantity:**

2

**Actuation Method:**

Push button

**End Application:**

Helicopter, mh-53e; aircraft, c-2a (reprocured); aircraft, tomcat f-14; aircraft, b-2 bomber (atb); helicopter, search and rescue, hh-60h; helicopter, carrier based asw, sh-60f; missile, minuteman lgm-30; helicopter, uscg search and rescue, hh-60j; aircraft, viking s-3b

**Grip Length:**

Between 1.200 inches and 1.220 inches

**Actuation Type:**

Push

**Hardness Rating:**

40.0 rockwell c spindle

**Shoulder To Head End Distance:**

0.890 inches

**Pin Attachment Type:**

Hook or ring

**Detent To Tapered End Distance:**

Between 0.260 inches and 0.290 inches

**Material:**

Steel comp 630 spindle or steel comp 632 spindle

**Material Specification:**

Ams 5643 assn standard 1st material response spindle or ams 5657 assn standard 2nd material response spindle

**Surface Treatment:**

Passivate spindle

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response spindle

**Style Designator:**

Button

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0