

View Online at <https://aerobasegroup.com/nsn/5315-00-725-4259>

**First End Style:**

Chamfered

**Second End Style:**

Chamfered

**Pinlength:**

Between 1.740 inches and 1.760 inches

**Pindiameter:**

Between 0.3115 inches and 0.3135 inches

**First End Taper Length:**

Between 0.0302 inches and 0.0322 inches

**Second End Taper Length:**

Between 0.115 inches and 0.135 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

39.0 rockwell c and 46.0 rockwell c

**First End Taper Angle:**

Between 44.5 degrees and 45.5 degrees

**Surface Finish:**

32.0 microinches

**Second End Taper Angle:**

Between 29.5 degrees and 30.5 degrees

**Material:**

Steel comp 416 or steel comp 416se

**Material Specification:**

Ams5610 assn standard 1st material response and astma582 assn standard 2nd material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.