

View Online at <https://aerobasegroup.com/nsn/5315-00-732-3006>

First End Style:

Chamfered

Second End Style:

Counterbored w/thru hole

Shank Length:

0.312 inches

Shoulder Diameter:

Between 0.8120 inches and 0.8125 inches

Shank Diameter:

Between 0.498 inches and 0.499 inches

Overall Length:

2.593 inches

Undercut Diameter:

0.370 inches

Undercut Width:

0.125 inches

Second Undercut Width:

0.125 inches

Second Undercut Diameter:

0.370 inches

First End Counterbore Diameter:

0.3281 inches

Second End Counterbore Diameter:

0.3281 inches

First End Counterbore Depth:

0.1562 inches

Second End Counterbore Depth:

0.156 inches

First End Taper Length:

0.031 inches

Second End Taper Length:

0.031 inches

Second End Relationship With First End:

Not identical

Second Shank Diameter:

0.812 inches

First End Location:

Short shank end

First End Taper Angle:

45.0 degrees

Criticality Code Justification:

Aavh and aaze

Surface Finish:

125.000 microinches

Second End Taper Angle:

45.0 degrees

Second Shank Length:

1.594 inches

Material:

Steel comp 1020

Surface Treatment:

Phosphate

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0