## NSN 5315-00-740-3905

Headed Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-740-3905

First Find Otube
First End Style: Chamfered
Head Style:
Flat
Under Head Length:
Between 0.740 inches and 0.760 inches
First Step Diameter:
Between 0.175 inches and 0.181 inches
First Step Length:
Between 0.078 inches and 0.0821 inches
Second Step Diameter:
Between 0.1235 inches and 0.1240 inches
Second Step Length: 0.678 inches
Hole Arrangement Style: One end drilled
First Hole Diameter:
Between 0.033 inches and 0.037 inches
Distance From Centerline Of Hole To End Of Pin:
0.102 inches
First End Taper Length:
Between 0.010 inches and 0.030 inches
Hardness Rating:
45.0 rockwell c and 50.0 rockwell c
First End Taper Angle:
Between 43.0 degrees and 47.0 degrees
Pin Head Diameter:
Between 0.245 inches and 0.255 inches
Surface Finish:
10.0 microinches large shank
Special Features:
First step flat 0.140 in. Across
Height:
Between 0.050 inches and 0.070 inches
Material:
Steel comp 615
Material Specification:
Ams 5616 assn standard single material response
Style Designator:
Shoulder
Shelf Life:
N/a

## NSN 5315-00-740-3905

Headed Shoulder Pin - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A212a0

