## NSN 5315-00-740-4845

Threaded Tapered Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-740-4845

| First End Style:   |
|--|
| Chamfered  |
| Thread Class:  |
| 2a   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| 0.970 inches   |
| Taper Length:  |
| 3.719 inches   |
| Taper Minor Diameter:  |
| Between 0.555 inches and 0.670 inches  |
| Taper Major Diameter:  |
| Between 1.243 inches and 1.248 inches  |
| Hole Arrangement Style:  |
| One end drilled  |
| First Hole Diameter:   |
| 0.1719 inches  |
| Distance From Centerline Of Hole To End Of Pin:  |
| 0.219 inches   |
| First End Taper Length:  |
| 0.047 inches   |
| Grip Length:   |
| 3.469 inches   |
| Thready Qty Per Inch (tpi):  |
| 16   |
| Second End Relationship With First End:  |
| Identical  |
| Thread Size:   |
| 0.750 inches   |
| Taper:   |
| 2.250 per foot in inches   |
| First End Location:  |
| Threaded end   |
| First End Taper Angle:   |
| 45.0 degrees   |
| Material:  |
| Steel comp 8645 handle or steel comp 8742 handle or steel comp 4140 handle or steel comp 4145 handle |
| Material Specification:  |
| Qq-s-624 federal specification all material responses handle   |
| Surface Treatment:   |
| Cadmium handle   |

## NSN 5315-00-740-4845

Threaded Tapered Pin - Page 2 of 2



## **Surface Treatment Specification:**

Qq-p-416 ty ii cl 2 federal specification single treatment response handle

**Style Designator:** 

Threaded at small end

**Thread Series Designator:** 

Unf

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A212a0