NSN 5315-00-740-9826

Headless Straight Pin - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5315-00-740-9826

| First End Style: |
|--|
| Chamfered |
| Hole Arrangement Style: |
| Both end drilled |
| First Hole Diameter: |
| Between 0.172 inches and 0.203 inches |
| Second Hole Diameter: |
| Between 0.172 inches and 0.203 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| Between 0.234 inches and 0.266 inches |
| Center To Center Distance Between Holes: |
| Between 3.484 inches and 3.516 inches |
| Pinlength: |
| Between 3.984 inches and 4.016 inches |
| Pindiameter: |
| Between 0.9980 inches and 1.0000 inches |
| First End Taper Length: |
| Between 0.047 inches and 0.078 inches |
| Second End Relationship With First End: |
| Identical |
| First End Taper Angle: |
| Between 44.0 degrees and 46.0 degrees |
| Material: |
| Steel comp 1140 or steel comp 1141 or steel comp 1144 |
| Material Specification: |
| Aisi assn standard single material response |
| Surface Treatment: |
| Phosphate zinc |
| Surface Treatment Specification: |
| Mil-p-16232 ty2 cl4 military specification single treatment response |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A212a0 |
| Mil-std (military Standard): |
| Mil-p-16232 spec. |
| |