NSN 5315-00-741-3296

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-741-3296

First Elid Style:ChamferedSecond End Style:OvalThread Class:2aThread Direction:Right-handThread Length:2.000 inchesShank Length:2.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.0622 inchesSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Thread endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesFirst End Taper Angle:Stol degreesSecond End Outer Radius:0.250 inchesSteelSurface Treatment:	Eirot End Styles
Second End Style:OvalThread Class:2aThread Direction:Right-handThread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.625 inchesSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.525 inchesFirst End Taper Angle:A.10 degreesSecond End Outer Radius:0.250 inchesFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesFirst End Taper Angle:Steel	First End Style:
OvalIhread Class:2aIhread Direction:Right-handIhread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.625 inchesGoed inchesFirst End Taper Length:0.625 inchesFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesSecond End Outer Radius:0.250 inches0.250 inches <td></td>	
Thread Class:2aThread Direction:Right-handThread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesHaterial:Steel	-
2a Thread Direction: Right-hand Thread Length: 2.000 inches Shank Length: 6.000 inches Shoulder Diameter: Between 1.000 inches and 1.005 inches Shoulder Diameter: Between 1.000 inches and 1.005 inches Shank Diameter: 0.625 inches Overall Length: 7.812 inches First End Taper Length: 0.625 inches Features Provided: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches	
Thread Direction:Right-handThread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesSecond End Relationship With First End:Not identicalFirst End Location:Threade endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inches	
Right-handThread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inches	
Thread Length:2.000 inchesShank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inches	
2.000 inches Shank Length: 6.000 inches Shoulder Diameter: Between 1.000 inches and 1.005 inches Shank Diameter: 0.625 inches Overall Length: 7.812 inches First End Taper Length: 0.062 inches First End Taper Length: Casehardened Second End Relationship With First End: Not identical First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches	-
Shank Length:6.000 inchesShoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesMaterial:Steel	-
6.000 inches Shoulder Diameter: Between 1.000 inches and 1.005 inches Shank Diameter: 0.625 inches Overall Length: 7.812 inches First End Taper Length: 0.062 inches Features Provided: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches	
Shoulder Diameter:Between 1.000 inches and 1.005 inchesShank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inches	
Between 1.000 inches and 1.005 inches Shank Diameter: 0.625 inches Overall Length: 7.812 inches First End Taper Length: 0.062 inches Features Provided: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	
Shank Diameter:0.625 inchesOverall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inches	
0.625 inches Overall Length: 7.812 inches First End Taper Length: 0.062 inches Features Provided: Casehardened Second End Relationship With First End: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	
Overall Length:7.812 inchesFirst End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesMaterial:Steel	
7.812 inches First End Taper Length: 0.062 inches Features Provided: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	
First End Taper Length:0.062 inchesFeatures Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesMaterial:Steel	-
0.062 inches Features Provided: Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	
Features Provided:CasehardenedSecond End Relationship With First End:Not identicalThread Size:0.625 inchesFirst End Location:Threaded endFirst End Taper Angle:45.0 degreesSecond End Outer Radius:0.250 inchesMaterial:Steel	
Casehardened Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	0.062 inches
Second End Relationship With First End: Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	Features Provided:
Not identical Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	
Thread Size: 0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	Second End Relationship With First End:
0.625 inches First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	Not identical
First End Location: Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	Thread Size:
Threaded end First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	0.625 inches
First End Taper Angle: 45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	First End Location:
45.0 degrees Second End Outer Radius: 0.250 inches Material: Steel	Threaded end
Second End Outer Radius: 0.250 inches Material: Steel	First End Taper Angle:
0.250 inches Material: Steel	45.0 degrees
Material: Steel	Second End Outer Radius:
Steel	0.250 inches
	Material:
Surface Treatment:	Steel
	Surface Treatment:
Cadmium	Cadmium
Surface Treatment Specification:	Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response	Qq-p-416, type 2, cl 3 federal specification single treatment response
Style Designator:	Style Designator:
Shoulder	Shoulder
Choulder	Thread Series Designator:
Choulder	Thread Series Designator:

Unf

NSN 5315-00-741-3296

Headless Shoulder Pin - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

