NSN 5315-00-754-1583

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-754-1583 First End Style: Chamfered **Second End Style:** Chamfered **Shank Length:** Between 0.167 inches and 0.177 inches Shoulder Diameter: Between 0.364 inches and 0.384 inches **Shank Diameter:** Between 0.3110 inches and 0.3115 inches **Overall Length:** Between 0.459 inches and 0.479 inches First End Taper Length: Between 0.006 inches and 0.026 inches **Second End Taper Length:** Between 0.021 inches and 0.041 inches Second End Relationship With First End: Not identical **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Second Shank Diameter:** Between 0.3110 inches and 0.3115 inches **First End Location:** Short shank end First End Taper Angle: Between 44.0 degrees and 46.0 degrees **Second End Taper Angle:** Between 44.0 degrees and 46.0 degrees Second Shank Length: Between 0.220 inches and 0.240 inches Material: Steel comp 410 **Material Specification:** Ams 5613 assn standard single material response **Surface Treatment: Passivate Style Designator:** Shoulder Shelf Life: N/a

--

Unit Of Measure:

NSN 5315-00-754-1583

Headless Shoulder Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0