

View Online at <https://aerobasegroup.com/nsn/5315-00-757-6303>

**First End Style:**

Chamfered

**Shank Length:**

Between 0.327 inches and 0.354 inches

**Shoulder Diameter:**

Between 0.594 inches and 0.625 inches

**Shank Diameter:**

Between 0.432 inches and 0.437 inches

**Overall Length:**

Between 1.250 inches and 1.281 inches

**Undercut Diameter:**

Between 0.402 inches and 0.417 inches

**Undercut Width:**

Between 0.047 inches and 0.063 inches

**Second Undercut Width:**

Between 0.047 inches and 0.063 inches

**Second Undercut Diameter:**

Between 0.402 inches and 0.417 inches

**First End Taper Length:**

Between 0.031 inches and 0.043 inches

**Second End Relationship With First End:**

Identical

**Second Shank Diameter:**

Between 0.462 inches and 0.467 inches

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Second Shank Length:**

Between 0.547 inches and 0.600 inches

**Special Features:**

0.266 in. Diameter hole drilled longitudinally through center axis of pin

**Material:**

Copper alloy 630

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A212a0