

View Online at <https://aerobasegroup.com/nsn/5315-00-762-9213>

First End Style:

Chamfered

Second End Style:

Pointed

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.400 inches

Shank Length:

0.712 inches

Shoulder Width Across Flats:

0.250 inches

Shank Diameter:

Between 0.184 inches and 0.190 inches

Overall Length:

1.212 inches

First End Taper Length:

0.047 inches

Second End Taper Length:

0.250 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

35.0 rockwell c and 43.0 rockwell c

Thread Size:

0.190 inches

Second Shank Diameter:

Between 0.214 inches and 0.215 inches

First End Location:

Threaded end

First End Taper Angle:

45.0 degrees

Surface Finish:

125.000 microinches

Second End Taper Angle:

30.0 degrees

Second Shank Length:

0.375 inches

Special Features:

0.063 in. Radius on shorter shank end

Material:

Steel comp 630

Material Specification:

Ams 5643, 17-4ph assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Mil-s-5002 military specification single treatment response

Style Designator:

Shoulder

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0

Mil-std (military Standard):

Mil-s-5002 spec.