NSN 5315-00-765-2137

Headless Shoulder Pin - Page 1 of 2



Headless Shoulder Pin - Page 1 of 2	,
View Online at https://aerobasegroup.com/nsn/5315-00-765-2137	
First End Style:	
Chamfered	
Second End Style:	
Square	
Shank Length:	
Between 0.180 inches and 0.195 inches	
Shoulder Diameter:	
Between 0.313 inches and 0.314 inches	
Shank Diameter:	
Between 0.310 inches and 0.311 inches	
Overall Length:	
Between 0.570 inches and 0.580 inches	
Undercut Diameter:	
Between 0.185 inches and 0.190 inches	
Undercut Width:	
0.031 inches	
Second Undercut Width:	
0.031 inches	
Second Undercut Diameter:	
Between 0.185 inches and 0.190 inches	
First End Taper Length:	
0.016 inches	
Second End Relationship With First End:	
Not identical	
Second Shank Diameter:	
Between 0.310 inches and 0.311 inches	
First End Location:	
Threaded end	
First End Taper Angle:	

45.0 degrees

Criticality Code Justification:

Abhp and abhp and abpa and aavh and aaze and aatr

Surface Finish:

125.000 microinches

Second Shank Length:

Between 0.180 inches and 0.195 inches

Special Features:

Hole 0.0120 dia, 1/8 inch deep drilled in center of square end

Material:

Steel comp 303

Material Specification:

Qq-s-763 federal specification single material response

NSN 5315-00-765-2137

Headless Shoulder Pin - Page 2 of 2



Style Designator:	
Undercut	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	

Fiig: A212a0