NSN 5315-00-773-2386

Headless Grooved Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-773-2386

| First End Style: |
|---|
| Square |
| Overall Length: |
| Between 4.047 inches and 4.078 inches |
| Diameter: |
| Between 1.246 inches and 1.250 inches |
| Effective Length: |
| Between 3.589 inches and 3.609 inches |
| Undercut Diameter: |
| Between 1.191 inches and 1.198 inches |
| Undercut Width: |
| Between 0.056 inches and 0.060 inches |
| Second Undercut Width: |
| Between 0.056 inches and 0.060 inches |
| Hole Arrangement Style: |
| Both end drilled |
| First Hole Diameter: |
| 0.156 inches |
| Second Hole Diameter: |
| 0.156 inches |
| Distance From Centerline Of Hole To End Of Pin: |
| 0.750 inches |
| Center To Center Distance Between Holes: |
| 2.437 inches |
| Second End Relationship With First End: |
| Identical |
| Hardness Rating: |
| 40.0 rockwell c and 48.0 rockwell c |
| First End Location: |
| Square end |
| Special Features: |
| Counterbored and tapped on one end |
| Material: |
| Steel comp 8640 or steel comp 4140 or steel comp 8740 |
| Material Specification: |
| Qq-s-624 federal specification all material responses |
| Style Designator: |
| Groove |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

--

NSN 5315-00-773-2386

Headless Grooved Pin - Page 2 of 2



Demilitarization:

No

Fiig:

A212a0