NSN 5315-00-779-4164

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-779-4164

RoundShank Length:Between 0.390 inches and 0.420 inchesShoulder Diameter:Between 0.334 inches and 0.354 inchesShank Diameter:Between 0.2525 inches and 0.2535 inchesOverall Length:Between 0.925 inches and 0.955 inchesUndercut Diameter:0.230 inchesBetween 0.010 inches and 0.030 inchesSecond Undercut Width:
Between 0.390 inches and 0.420 inches Shoulder Diameter: Between 0.334 inches and 0.354 inches Shank Diameter: Between 0.2525 inches and 0.2535 inches Overall Length: Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Shoulder Diameter: Between 0.334 inches and 0.354 inches Shank Diameter: Between 0.2525 inches and 0.2535 inches Overall Length: Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Between 0.334 inches and 0.354 inches Shank Diameter: Between 0.2525 inches and 0.2535 inches Overall Length: Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Shank Diameter:Between 0.2525 inches and 0.2535 inchesOverall Length:Between 0.925 inches and 0.955 inchesUndercut Diameter:0.230 inchesUndercut Width:Between 0.010 inches and 0.030 inches
Between 0.2525 inches and 0.2535 inches Overall Length: Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Overall Length: Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Between 0.925 inches and 0.955 inches Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Undercut Diameter: 0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
0.230 inches Undercut Width: Between 0.010 inches and 0.030 inches
Undercut Width: Between 0.010 inches and 0.030 inches
Between 0.010 inches and 0.030 inches
Second Undercut Width:
Between 0.010 inches and 0.030 inches
Second Undercut Diameter:
0.230 inches
Second End Relationship With First End:
Identical
Hardness Rating:
26.0 rockwell c and 32.0 rockwell c
Second Shank Diameter:
Between 0.2560 inches and 0.2565 inches
First End Location:
Both ends
First End Outer Radius:
0.080 inches
Surface Finish:
63.0 microinches large shank
Second Shank Length:
Between 0.445 inches and 0.475 inches
Special Features:
Ends 32.0 microinch finish
Material:
Steel comp 416f
Material Specification:
Ams 5610 assn standard single material response
Style Designator:
Undercut
Shelf Life:
N/a

NSN 5315-00-779-4164

Headless Shoulder Pin - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A212a0

