## NSN 5315-00-779-4164

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-779-4164 First End Style: Round **Shank Length:** Between 0.390 inches and 0.420 inches Shoulder Diameter: Between 0.334 inches and 0.354 inches **Shank Diameter:** Between 0.2525 inches and 0.2535 inches **Overall Length:** Between 0.925 inches and 0.955 inches **Undercut Diameter:** 0.230 inches **Undercut Width:** Between 0.010 inches and 0.030 inches **Second Undercut Width:** Between 0.010 inches and 0.030 inches **Second Undercut Diameter:** 0.230 inches Second End Relationship With First End: Identical **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Second Shank Diameter:** Between 0.2560 inches and 0.2565 inches **First End Location:** Both ends First End Outer Radius: 0.080 inches Surface Finish: 63.0 microinches large shank **Second Shank Length:** Between 0.445 inches and 0.475 inches **Special Features:** Ends 32.0 microinch finish Material: Steel comp 416f **Material Specification:** Ams 5610 assn standard single material response **Style Designator:** Undercut Shelf Life:

N/a

## NSN 5315-00-779-4164

Headless Shoulder Pin - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A212a0