# NSN 5315-00-780-7536

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-780-7536

## Head Style:

Pan no. 2 (r1 not required in item description)

# Chamfer Length:

Between 0.077 inches and 0.109 inches

# Diameter:

Between 0.994 inches and 0.996 inches

## Under Head Length:

Between 2.053 inches and 2.073 inches

# Hole Arrangement Style:

One end drilled

#### First Hole Diameter:

Between 0.161 inches and 0.181 inches

# Distance From Centerline Of Hole To End Of Pin:

0.196 inches

#### Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

#### **Pin Chamfer Angle:**

Between 14.5 degrees and 15.5 degrees

# Shear Strength:

117820 double pound

## **Pin Head Diameter:**

Between 1.171 inches and 1.203 inches

#### **Special Features:**

Shank end may have either a chamfer or radius at the option of the vendor

#### Height:

Between 0.109 inches and 0.141 inches

#### Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

#### Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification

3rd material response

#### Surface Treatment:

Cadmium and chromate

#### **Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### Style Designator:

Straight

## Shelf Life:

N/a

#### Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5315-00-780-7536

Headed Straight Pin - Page 2 of 2

Fiig: A212a0 Mil-std (military Standard): Mil-s-6758 spec.

