

View Online at <https://aerobasegroup.com/nsn/5315-00-785-5344>

First End Style:

Radius

Second End Style:

Radius

Shank Length:

Between 0.390 inches and 0.420 inches

Shoulder Diameter:

0.344 inches

Shank Diameter:

Between 0.2495 inches and 0.2505 inches

Overall Length:

Between 0.925 inches and 0.955 inches

Undercut Diameter:

0.230 inches

Undercut Width:

0.020 inches

Second Undercut Width:

0.020 inches

Second Undercut Diameter:

0.230 inches

First End Corner Radius:

Between 0.1247 inches and 0.1252 inches

Second End Corner Radius:

Between 0.1265 inches and 0.1272 inches

Second End Relationship With First End:

Not identical

Hardness Rating:

26.0 rockwell c and 32.0 rockwell c

Second Shank Diameter:

Between 0.2530 inches and 0.2535 inches

First End Location:

Both ends

Surface Finish:

63.000 microinches

Second Shank Length:

Between 0.445 inches and 0.475 inches

Material:

Steel comp 416f

Material Specification:

Ams 5610 assn standard single material response

Surface Treatment:

Passivate

Style Designator:

Undercut

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0