

View Online at <https://aerobasegroup.com/nsn/5315-00-785-5344>

**First End Style:**

Radius

**Second End Style:**

Radius

**Shank Length:**

Between 0.390 inches and 0.420 inches

**Shoulder Diameter:**

0.344 inches

**Shank Diameter:**

Between 0.2495 inches and 0.2505 inches

**Overall Length:**

Between 0.925 inches and 0.955 inches

**Undercut Diameter:**

0.230 inches

**Undercut Width:**

0.020 inches

**Second Undercut Width:**

0.020 inches

**Second Undercut Diameter:**

0.230 inches

**First End Corner Radius:**

Between 0.1247 inches and 0.1252 inches

**Second End Corner Radius:**

Between 0.1265 inches and 0.1272 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Second Shank Diameter:**

Between 0.2530 inches and 0.2535 inches

**First End Location:**

Both ends

**Surface Finish:**

63.000 microinches

**Second Shank Length:**

Between 0.445 inches and 0.475 inches

**Material:**

Steel comp 416f

**Material Specification:**

Ams 5610 assn standard single material response

**Surface Treatment:**

Passivate

**Style Designator:**

Undercut

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0