NSN 5315-00-794-8600

Round

Headless Shoulder Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-794-8600 First End Style:

| Second End Style: |
|---|
| Square |
| Thread Class: |
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.312 inches |
| Shank Length: |
| Between 0.368 inches and 0.384 inches |
| Shoulder Diameter: |
| Between 0.185 inches and 0.189 inches |
| Shank Diameter: |
| 0.112 inches |
| Overall Length: |
| Between 0.839 inches and 0.849 inches |
| Second End Relationship With First End: |
| Not identical |
| Thread Size: |
| 0.112 inches |
| Second Shank Diameter: |
| Between 0.123 inches and 0.127 inches |
| First End Location: |
| Threaded end |
| First End Outer Radius: |
| Between 0.092 inches and 0.094 inches |
| Surface Finish: |
| 125.000 microinches |
| Second Shank Length: |
| Between 0.429 inches and 0.441 inches |
| Material: |
| Copper alloy 360 or copper alloy 464 |
| Surface Treatment: |
| Nickel |
| Surface Treatment Specification: |
| Amph 676 fscm 02660 mfr ref single treatment response |
| Style Designator: |
| Shoulder |
| Thread Series Designator: |
| Unc |

NSN 5315-00-794-8600

Headless Shoulder Pin - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0