NSN 5315-00-801-7255

Headless Shoulder Pin - Page 1 of 2

Between 0.074 inches and 0.080 inches

First End Style:

Second End Style:

Shank Length:

Chamfered

Square



View Online at https://aerobasegroup.com/nsn/5315-00-801-7255

Shoulder Diameter:
Between 0.173 inches and 0.179 inches
Shank Diameter:
Between 0.0572 inches and 0.0577 inches
Overall Length:
0.464 inches
Undercut Diameter:
Between 0.0792 inches and 0.0797 inches
Undercut Width:
0.032 inches
Second Undercut Width:
0.032 inches
Second Undercut Diameter:
Between 0.0792 inches and 0.0797 inches
First End Taper Length:
Between 0.010 inches and 0.020 inches
Second End Relationship With First End:
Not identical
Hardness Rating:
35.0 rockwell c and 45.0 rockwell c
Second Shank Diameter:
Between 0.0892 inches and 0.0897 inches
First End Location:
Long end
First End Taper Angle:
15.0 degrees
Second Shank Length:
Between 0.284 inches and 0.290 inches
Material:
Steel comp 416f
Material Specification:
Ams 5610 assn standard single material response
Surface Treatment:
Passivate
Style Designator:
Undercut

NSN 5315-00-801-7255

Headless Shoulder Pin - Page 2 of 2



C	ha	Ιf	1	ife	
•	ııe		_	.II C	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A212a0