## NSN 5315-00-811-1267

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-811-1267

## Head Style:

Pan no. 2 (r1 not required in item description)

#### Chamfer Length:

0.062 inches

## Diameter:

Between 0.122 inches and 0.124 inches

#### Under Head Length:

Between 0.835 inches and 0.855 inches

## Hole Arrangement Style:

One end drilled

#### First Hole Diameter:

Between 0.060 inches and 0.080 inches

#### Distance From Centerline Of Hole To End Of Pin:

0.091 inches

#### Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

#### Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

#### Pin Head Diameter:

Between 0.234 inches and 0.266 inches

## Special Features:

The shank end of pin may have either a chamfer or radius at the option of the vendor

## Height:

Between 0.030 inches and 0.062 inches

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

## Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification

3rd material response

## Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

#### Style Designator:

Straight

Shelf Life:

N/a

## Unit Of Measure:

--

## Demilitarization:

No

Fiig:

A212a0

# NSN 5315-00-811-1267

Headed Straight Pin - Page 2 of 2

## Mil-std (military Standard):

Mil-s-6758 spec.

