

View Online at <https://aerobasegroup.com/nsn/5315-00-812-3775>

**Head Style:**

Pan no. 2 (r1 not required in item description)

**Chamfer Length:**

0.062 inches

**Diameter:**

Between 0.122 inches and 0.124 inches

**Under Head Length:**

Between 0.897 inches and 0.917 inches

**Hole Arrangement Style:**

One end drilled

**First Hole Diameter:**

Between 0.060 inches and 0.080 inches

**Distance From Centerline Of Hole To End Of Pin:**

0.091 inches

**Hardness Rating:**

26.5 rockwell c and 32.0 rockwell c

**Pin Chamfer Angle:**

Between 14.5 degrees and 15.5 degrees

**Pin Head Diameter:**

Between 0.234 inches and 0.266 inches

**Special Features:**

The shank end of pin may have either a chamfer or radius at the option of the vendor

**Height:**

Between 0.030 inches and 0.062 inches

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630

**Material Specification:**

Ams 6300 assn standard 1st material response or mil-t-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2 cl 2 federal specification single treatment response

**Style Designator:**

Straight

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-t-6758 spec.