NSN 5315-00-812-7424

Headed Straight Pin - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5315-00-812-7424

| | | • | |
|------|-----|-----|----|
| ш | nod | Stv | Δ. |
| 1 15 | zau | JLV | œ. |

Pan no. 2 (r1 not required in item description)

Chamfer Length:

Between 0.062 inches and 0.094 inches

Diameter:

Between 0.745 inches and 0.747 inches

Under Head Length:

Between 4.194 inches and 4.214 inches

Hole Arrangement Style:

One end drilled

First Hole Diameter:

Between 0.131 inches and 0.151 inches

Distance From Centerline Of Hole To End Of Pin:

0.165 inches

Hardness Rating:

26.5 rockwell c and 32.0 rockwell c

Pin Chamfer Angle:

Between 14.5 degrees and 15.5 degrees

Shear Strength:

66280 double pound

Pin Head Diameter:

Between 0.859 inches and 0.891 inches

Special Features:

Shank end may have either a chamfer or radius at the option of the vendor

Height:

Between 0.077 inches and 0.109 inches

Material:

Steel comp 4037 or steel comp 4130 or steel comp 8630

Material Specification:

Ams 6300 assn standard 1st material response or mil-s-6758 military specification 2nd material response or mil-s-6050 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2 cl 2 federal specification single treatment response

Style Designator:

Straight

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

NSN 5315-00-812-7424

Headed Straight Pin - Page 2 of 2



Fiig:

A212a0

Mil-std (military Standard):

Mil-s-6758 spec.