

View Online at <https://aerobasegroup.com/nsn/5315-00-815-4854>

**First End Style:**

Chamfered

**Second End Style:**

Pointed

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.330 inches

**Shank Length:**

Between 0.278 inches and 0.281 inches

**Shoulder Width Across Flats:**

0.500 inches

**Shank Diameter:**

Between 0.224 inches and 0.225 inches

**Overall Length:**

0.750 inches

**First End Taper Length:**

0.050 inches

**Second End Taper Length:**

0.094 inches

**Second End Relationship With First End:**

Not identical

**Hardness Rating:**

35.0 rockwell c and 43.0 rockwell c

**Thread Size:**

0.250 inches

**Second Shank Diameter:**

Between 0.2435 inches and 0.2500 inches

**First End Location:**

Threaded end

**First End Taper Angle:**

45.0 degrees

**Surface Finish:**

125.000 microinches

**Second End Taper Angle:**

45.0 degrees

**Second Shank Length:**

Between 0.409 inches and 0.412 inches

**Material:**

Steel comp 630

**Material Specification:**

Ams 5643 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Mil-s-5002 military specification single treatment response

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5002 spec.