

View Online at <https://aerobasegroup.com/nsn/5315-00-815-9400>

**Head Diameter:**

Between 0.490 inches and 0.610 inches

**Shank Diameter:**

Between 0.3720 inches and 0.3735 inches

**Detent Quantity:**

2

**Grip Length:**

Between 2.100 inches and 2.120 inches

**Actuation Type:**

Pull and push

**Shear Strength:**

18400 double pounds per square inch

**Shoulder To Head End Distance:**

Between 0.620 inches and 0.720 inches

**Pin Center To Handle End Distance:**

Between 0.820 inches and 0.920 inches

**Pin Attachment Type:**

Hook

**Detent To Tapered End Distance:**

Between 0.290 inches and 0.390 inches

**Material:**

Steel comp 4130 spindle

**Material Specification:**

Mil-t-6736 military specification single material response shank or mil-s-6758 military specification single material response shank

**Surface Treatment:**

Cadmium spindle and chromate spindle

**Surface Treatment Specification:**

Qq-p-416, type 2, cl 2 federal specification single treatment response spindle

**Style Designator:**

Cam lever

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-6758 spec.