

View Online at <https://aerobasegroup.com/nsn/5315-00-824-2292>

**First End Style:**

Chamfered

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.824 inches

**Shank Length:**

0.625 inches

**Shoulder Diameter:**

0.750 inches

**Shank Diameter:**

Between 0.360 inches and 0.370 inches

**Overall Length:**

1.687 inches

**First End Taper Length:**

Between 0.031 inches and 0.062 inches

**Second End Relationship With First End:**

Identical

**Hardness Rating:**

39.0 rockwell c and 42.0 rockwell c

**Thread Size:**

0.375 inches

**Second Shank Diameter:**

Between 0.3735 inches and 0.3745 inches

**First End Location:**

Both ends

**First End Taper Angle:**

45.0 degrees

**Second Shank Length:**

0.906 inches

**Material:**

Steel comp e4340 or steel comp 4340

**Material Specification:**

Mil-s-5000 military specification all material responses

**Surface Treatment:**

Cadmium

**Style Designator:**

Shoulder

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A212a0

**Mil-std (military Standard):**

Mil-s-5000 spec.